



Hinges Full Mortise Hinges - Standard Weight

Full mortise hinge for use on medium weight doors that have medium to high frequency service. They are suitable for hollow metal or wood doors.



FI179BB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight 5 Knuckle 2 ball bearing hinges Steel

Sizes:	Inches	mm	Inches	mm
4-1/2" x 4"		(114X102)	.134	(3.4)
4-1/2" x 4-1/2"		(114X114)	.134	(3.4)
5" x 4"		(127X102)	.146	(3.7)
5" x 4-1/2"		(127X114)	.146	(3.7)
5" x 5"		(127X127)	.146	(3.7)

Finishes: US26, US26D, US10B

Options: NRP/ETW/PIC/RC

cUL Listing stamp for fire

See page 15-17 for details



FI191BB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight 5 Knuckle 2 ball bearing hinges Stainless Steel

Sizes:	Inches	mm	Inches	mm
4-1/2" x 4"		(114X102)	.134	(3.4)
4-1/2" x 4-1/2"		(114X114)	.134	(3.4)
5" x 4"		(127X102)	.146	(3.7)
5" x 4-1/2"		(127X114)	.146	(3.7)
5" x 5"		(127X127)	.146	(3.7)

Finishes: US32D

Options: NRP/ETW/PIC/RC/HT

cUL Listing stamp for fire

See page 15-17 for details