



3000 Series Tubular



Tubular sets are designed for standard duty commercial and high end residential projects

Passage Sets

Privacy

Single and double dummy sets

2-3/8" and 2-3/4" Backset

WH listed for 20 minute doors available

FEATURES

All trims are compatible with 8700 Series Mortise locks for hybrid (mortise lock and tubular) applications The 3000 Series fire rated latchbolt is engineered to the rigorous standards of WH for use on 20 Minute Fire labeled doors

The 3000 Series is user friendly and easy to operate

Suitable for a myriad of applications including offices, residential single family and multi-family applications

SPECIFICATIONS

Door Thickness	For Doors 1-3/8" to 1-3/4" thick (35mm to 45mm)
Backset	2-3/8" (60mm) or 2-3/4" (70mm) standard
Strike	Full lip strike standard
Hand	None handed passage and privacy sets. Some designs are handed when used as dummies
Latchbolt	1/2" throw standard
Finish	Standard finishes include US32D (630) and US15 (619). Other finishes available upon request. Split finishes also available. Please consult your representative or customer service for more information
Listing	Warnock Hersey/Intertek listed for use on Fire Doors (20 minute rated)







3000 Series Functions

NON KEYED

PART NUMBER FUNCTION

FI3001	Passage
FI3022	Privacy
FI3093	Single Dummy
FI3094	Double Dummy

3000 Series Standard Lock Functions

Illustration	Deadbolt Functions	Function	Description
	FI3001	Passage	Latchbolt retracted by lever on either side
	FI3022	Privacy	Push-button locks outside lever Turning inside lever or pushing emergency release unlocks outside lever Inside lever always active
	FI3093	Half Dummy Trim	Single dummy trim for one side of door Used for door pull as matching inactive trim
	FI3094	Double Dummy Trim	Double dummy for both sides of door Used for door pulls as matching inactive trim