



## Full Mortise Hinges - Standard Weight - Economy Hinge

Full mortise hinge for use on medium weight doors that have medium frequency service. They are suitable for hollow metal or wood doors.



### FI603BB

Certification: Conforms to A156.7

Description: Standard Weight 5 Knuckle 2 ball bearing hinges Steel

Sizes:	Inches	mm	Inches	mm
4-1/2" x 4"		(114X102)	.134	(3.4)
4-1/2" x 4-1/2"		(114X114)	.134	(3.4)

Finishes: US26D

Options: NRP/RC

See page 15-16 for details

## Full Mortise Hinges - Standard Weight - Spring Hinge

Fully adjustable; spring tension may be increased or decreased during installation. Apartments, hotel or motel rooms, condominiums and office buildings or anywhere self closing doors are required. Use 2 spring hinges on fire doors, centre and bottom location. All other applications: Up to 70lbs, 1 spring hinge with 2 ball bearing hinges. Spring hinge in centre. Up to 90lbs, 2 spring hinges with 1 ball bearing hinge. Spring hinge in centre and bottom. Up to 120lbs, 3 spring hinges.



### FI606SH

Certification: ANSI/BHMA A156.17

Description: Standard Weight, Spring hinges Steel

Sizes:	Inches	mm	Inches	mm
4-1/2" x 4"		(114X102)	.134	(3.4)
4-1/2" x 4-1/2"		(114X114)	.134	(3.4)

Finishes: US26D

Options: RC

See page 16 for details